

## Product data sheet

## HSBW200

### Characteristics

Voltage stabilizer, HSJW, servo motor type, 200 kVA, dial meter display, 304...456 V input, 380 V output



Product Image Coming Soon

### Main

|                           |                    |
|---------------------------|--------------------|
| Range of product          | HSBW               |
| Product or component type | Voltage stabilizer |
| Technology type           | Servo motor        |
| Provided equipment        | User manual        |

### Complementary

|  |   |
|--|---|
| Rated power in VA                      | 200 kVA   |
| Minimum insulating resistance          | 5 MOhm  |
| Efficiency                             | 95 %  |
| Optional feature                       | Bypass<br>Cooling fan   |
| Protection type                        | Overvoltage for output<br>Undervoltage protection for output<br>Undervoltage protection optional for input<br>Overload protection optional<br>Phase failure optional<br>Temperature rise protection optional<br>Time delay optional<br>Inrush surge protection optional |
| Signalling function                    | Dial pointer indication   |
| Output voltage                         | 380 V AC +/- 3 %  |
| Network frequency                      | 50/60 Hz  |
| [Uimp] rated impulse withstand voltage | 2 kV per minute   |

### Environment

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...40 °C                                 |
| Relative humidity                     | 0...90 %                                   |
| Operating altitude                    | 0...2000 m                                 |
| Standards                             | EN 61000-6-2<br>EN 61000-6-4<br>EN 61558-1 |

### Offer Sustainability

|                       |    |
|-----------------------|----|
| Sustainable packaging | No |
|-----------------------|----|